

# Wall-Mountable Interconnect Center (WIC)

A LANscape®  
Solutions Product

## features and benefits |

<b>Patented universal cable clamp</b>	Cable strain-relief
<b>Durable metal housing</b>	Protection
<b>Lockable doors</b>	System security
<b>Routing guides</b>	Fiber management

The Corning Cable Systems Wall-Mountable Interconnect Center (WIC) is an economical housing for terminating optical fiber cables. It provides protection for the connectors in the physical plant environment and is ideal for use in building entrance rooms, telecommunication rooms, or inside programmable logic controller cabinets typically found in manufacturing plants. The durable black metal housing can be mounted in stacked and/or reversed positions and there is an optional cover available for jumper protection with lockable doors. Strain-relief is accomplished with the patented universal cable clamp and routing guides are included for fiber management.

The WIC-02P accepts two standard CCH connector panels and the WIC-04P accepts four panels or modules. Both housings include splicing provisions for Corning Cable Systems Type 2R or 4R splice trays and accept the standard CCH connector panels, CCH pigtail panels or CCH Plug & Play™ Systems connector modules.



# Wall-Mountable Interconnect Center (WIC)

A LANscape®  
Solutions Product

## specifications |

	Dimensions (H x W x D) cm (in)	Shipping Weight kg (lb)
<b>WIC-02P</b>	33 x 21.6 x 6.6 (13 x 8.5 x 2.6)	2.3 (5)
<b>WIC-04P</b>	33 x 21.6 x 10.4 (13 x 8.5 x 4.1)	2.7 (6)
<b>WIC2-DOOR</b>	33 x 8.9 x 6.6 (13 x 3.5 x 2.6)	0.9 (2)
<b>WIC4-DOOR</b>	33 x 8.9 x 10.4 (13 x 3.5 x 4.1)	1.1 (2.5)

## ordering information |

Part Number	Description
<b>WIC-02P</b>	Wall-Mountable Interconnect Center; accepts 2 LANscape® Solutions CCH Connector Panels or Modules, and a maximum of (4) 0.2-in or (2) 0.4-in reduced-length splice trays; supplied with 1 CCH blank panel
<b>WIC-04P</b>	Wall-Mountable Interconnect Center; accepts 4 LANscape Solutions CCH Connector Panels or Modules, and a maximum of (8) 0.2-in or (4) 0.4-in reduced-length splice trays; supplied with 3 CCH blank panels

### Accessories

<b>WIC2-DOOR</b>	Jumper Protection Door for the WIC-02P; includes installation hardware
<b>WIC4-DOOR</b>	Jumper Protection Door for the WIC-04P; includes installation hardware
<b>HDWR-LOCK-KIT</b>	Field-Installable Lock; includes 1 lock and key
<b>HDWR-LOCK-KIT-2</b>	Field-Installable Lock; includes 1 lock and key; keyed different from HDWR-LOCK-KIT
<b>CCH-BLNK</b>	Blank Panel, compatible with LANscape Solutions housings
<b>WCH-STRNRLF-KIT</b>	Cable Strain-Relief Kit for WIC-02P/-04P; includes 1 universal cable clamp (UCC) and mounting bracket

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA  
800-743-2675 • FAX: 828-901-5973 • International: +1-828-901-5000 • [www.corning.com/cablesystems](http://www.corning.com/cablesystems)

Corning Cable Systems reserves the right to improve, enhance and modify the features and specifications of Corning Cable Systems products without prior notification. LANscape is a registered trademark of Corning Cable Systems Brands, Inc. Plug & Play is a trademark of Corning Cable Systems Brands, Inc. All other trademarks are the properties of their respective owners. Corning Cable Systems is ISO 9001 certified. © 2004, 2008 Corning Cable Systems. All rights reserved. Published in the USA. LAN-570-EN / May 2008