

Index

ATM	3.2, 3.7, 3.8
Adapter Type	8.12
Aerial Cable	2.24, 5.4-5.5
All-Dielectric Cable	1.1, 5.3, 5.4
Anaerobic	7.7
Applications	3.1
Armored Cable	5.4
Array Connector Polarity	2.8
Attenuation	5.8, 10.1-10.4, 10.7, 10.8, 10.10-10.12
BICSI	2.22
Backbone Cabling	2.4, 2.5, 10.10
Bandwidth	2.1, 4.8, 5.8, 10.1
Bend Radius (See Minimum Bend Radius)	
Buffer Tube Fan-Out Kit (See Fan-Out Kits)	
Building Backbone	2.5, 2.14, 2.15, 2.17, 3.6, 4.5, 5.3, 5.5, 8.2, 8.8
Building Codes	2.23
Cable Applications and Selection	5.3-5.7
Cable Assemblies	7.2
Fan-Out	7.7
Jumper Method	2.8
Patch Cords	5.7
Preterminated Cable and Hardware	9.1-9.17
Cable, Fiber Optic	
ALTOS® Cable	5.3, 5.4
Figure-8 ALTOS Cable	5.4
FREEDM® Cable	5.6
Limited Smoke, Zero Halogen (LSZH™) Cable	5.5
Loose Tube	5.2
MIC® and MIC Unitized Cables	5.5
Single-Fiber Cable	5.8
SST™ Ribbon Cables	5.2
Zipcord Cable	5.8
Cabling	2.15-2.18
Campus Backbone	1.2, 2.12, 4.5, 5.3
Centralized	3.6, 8.3, 8.7
Horizontal	1.3, 2.5, 2.15, 2.16
Cable Records	10.13
Cable System Testing	10.1
Campus Backbone Cables	5.3
Fiber Zone Box (FZB)	8.8
Center Wavelength	3.3
Centralized Backbone Cabling	4.18, 4.19
Centralized Cabling	2.16, 8.3, 8.7
Closet Distribution Frame	8.2, 8.5
Connector Panels	8.5-8.7
Connector Polarity	2.6
Connectors	
Epoxy and Polish	7.6
No-Epoxy/No-Polish (UniCam® Connectors)	7.5
FC	7.4-7.6
LC	7.1, 7.4, 7.5, 7.7-7.9
MTP® Connector	7.2, 7.9, 9.11
MT-RJ	7.5, 7.6
SC	7.1, 7.4-7.8
ST® Compatible Connector	7.4-7.6, 7.8, 7.9
UV-Cured	7.6
Connector Panels/Modules and Splicing	8.5-8.7
Consolidation Splice	2.20
Data Centers	9.1-9.17
Data Center Environment	9.8
Data Center Spaces and Infrastructure	9.2
Data Communications	4.2
Data Rate	3.3, 3.4
Decentralized Backbone Network	4.18
Direct Buried Cable	2.25
Dispersion	10.11
Documentation	10.1-10.15
Duct Utilization	2.22
Duplex	4.1
Duplex Connector Polarity	2.6
Dynamic Range	3.4
Electromagnetic Interference (EMI)	1.1
End-to-End Attenuation Testing	10.4-10.7
End Equipment	3.2
Equipment Cables	1.6, 5.8
Equipment Room	2.18
Ethernet	2.2, 3.1, 4.5, 4.6
Extender Trunks	9.12
FDDI	3.1, 3.2
FWHM (Full Width Half Maximum)	3.3
Fan-Out Kits	7.7, 8.14
Ferrule(s)	7.3

Index

- Fiber Count 4.1-4.20
- Fiber Distribution Data Interface (See FDDI)
- Fiber Optic Cable (See Cable, Fiber Optic)
- Fiber-to-the-Desktop 1.3
- Fiber Type 8.12
- Fibre Channel 2.1, 3.1, 3.7, 3.8
- Field Termination 7.3
- Fill Ratio 2.23
- Fire Codes 2.23
- Full Width Half Maximum (See FWHM)
- Fusion Splicing 6.1
- Future Growth 4.3
- Grounding 5.10
- Hardware 8.1-8.16, 9.14
 - Intermediate Cross-Connect (IC) 2.4, 2.12, 2.14, 4.5-4.9, 4.11, 8.2
 - Main Cross-Connect (MC) 2.12, 2.14, 4.5-4.9, 4.11, 8.1, 8.2, 8.3
 - Preterminated Cables and Hardware 9.1-9.17
 - Splicing 8.5-8.8
 - Telecommunications Outlet 8.9
- Harnesses 9.13
- Heat-Cured 7.6
- Hierarchical Star (See Physical Hierarchical Star)
- Horizontal Cabling 2.1, 2.15, 10.7, 10.10
- Horizontal Cross-Connect (HC) 2.5, 2.12, 2.14, 2.15, 2.18, 4.6, 8.2, 8.3
- Hybrid Assemblies 7.2
- IC 2.4, 2.12, 2.14, 4.5-4.9, 4.11, 5.5, 8.2, 8.3
- IEEE 3.1, 5.5
- Indoor/Outdoor Cables 5.4
- Insertion Loss 7.4, 9.17
- Installation Considerations 2.1-2.25, 5.8
- Intermediate Cross-Connect (See IC)
- Jumpers (See Cable Assemblies)
- LAN (Local Area Network) 9.1
- LANscape® Solutions 1.6
- Light Emitting Diode (LED) 3.2, 3.3, 3.5
- Local Area Network (See LAN)
- Logical Bus 2.2
- Logical Mesh 2.3
- Logical Star 2.1, 2.2
- Logical Point-to-Point 2.1, 2.2
- Logical Topology 2.1, 2.3
- Loose Tube Cable 5.2
- Main Cross-Connect (See MC)
- Maintenance and Troubleshooting 10.13-10.15
- Mandrel Wrapping 10.3
- Mass Splicing 6.3
- Maximum Tensile Rating 2.21
- Maximum Vertical Rise 2.21
- MC (Main Cross-Connect) 2.4, 2.5, 2.12, 2.14, 4.5-4.9, 4.11, 8.1-8.3
- Mechanical Splice (CamSplice™ Mechanical Splice) 6.4
- Mesh 4.8
- Midspan Access 2.21
- Minimum Bend Radius 2.21
- Modules 8.12
- Multimode 3.1, 3.2, 3.4-3.6
- Multiple Cables 2.19
- Multiple Sheaths and Splice Points 2.19
- Multiuser Outlet Cabling 2.17
- Multiuser Workstations 5.7
- MUTOA 2.6, 2.16, 2.17, 4.19
- National Electrical Code® (See NEC®)
- NEC® (National Electrical Code®) 2.23, 5.8-5.10, 8.8
- NEMA 8.10
- Network Traffic Analysis 4.3
- Network 3.1, 3.2
- Operating Wavelengths 3.4
- Optical Fiber Termination Spaces 2.24
- Optical Return Loss 10.11
- OTDR 10.1, 10.8-10.10, 10.13
- OTDR Signature Traces 10.13
- OTDR Signature Trace Documentation 10.8
- Outdoor Hardware 8.10
 - Environmental Distribution Center (EDC) 8.10, 8.16
 - Industrial Connector Housing 8.10
 - Splice Closures 8.4
- Outlets 8.1-8.16
- Pair-Flip Trunk Method 2.8
- Panel Density 8.12
- Patch Cords 1.6, 5.8, 9.13
- Patch Panels 8.12
- Pathways and Spaces 2.22
- Percentage Rules 4.4

Index

Physical Hierarchical Star	2.1
Physical Ring	2.3, 2.13
Physical Star (See Physical Hierarchical Star)	
Physical Topology	2.3
Pigtail Splicing	7.1
Pigtails (See Cable Assemblies)	
Plug & Play™ Universal Systems Pulling Grip	9.11
Point-to-Point	2.1
Point-to-Point Redundant Star	4.7
Polarity	2.6-2.8, 9.17
Preterminated Assemblies	7.2
Preterminated Cables and Hardware	9.1-9.17
Plug & Play Universal Systems	9.10
Pulling Grip	9.12
Preterminated Solutions	9.9
Private Branch Exchange (PBX)	1.2
Rack-Mountable Hardware	8.4, 8.5
Closet Connector Housing	8.5
Closet Distribution Frame	8.5
Closet Splice Housing	8.6
Connector Panel	8.5-8.7
Receivers	3.3
Redundancy Over a Physical Star	4.7
Redundant Electronics	2.4
Redundant Point-to-Multipoint Star	4.14
Redundant Routings	2.4
Reflectance	7.4
Reverse-Pair Positioning	2.7
Ribbon Fan-Out Kit	7.8
Ring	2.2
Rise Time	3.4
Secure Government and Military Applications	1.5
Security Video	2.2, 4.2
Self-Supporting Aerial Cables	5.4
Sensors	4.2
Simplex Connector Polarity	2.6
Single-mode	3.1, 3.4
Single-mode Fiber Planning	4.2
Single-User Workstations	5.7
SMH (See Splice Module Housing)	
SONET (Synchronous Optical Network)	3.2
Specifications, Optical Fiber	3.5, 3.6
Spectral Width	3.3
Spider Fan-Out Kit	7.8
Splice Closures	8.4
Splice Loss	6.2, 10.10
Splice Points	2.20
Splice Protection	6.4
Splice Trays	8.13
Splicing	6.1-6.6, 7.1
Splicing, Fusion	
miniMass® Micro Fusion Splicer	6.3
Splicing, Mechanical	6.4
Star	2.2
Structured Cabling	2.1
System Planning	1.1, 1.2
Telecommunications Enclosure	2.18
TR (Telecommunications Room)	2.18
TIA/EIA-492AAAA, TIA/EIA-492AAAB, TIA/EIA-492CAAB	3.5
Detailed specification for 50 µm, 62.5 µm MM fiber and single-mode fibers	
TIA/EIA-492AAAC	3.4, 3.5
Detailed specification for 50 µm mm fiber	
TIA/EIA 568-B	2.4, 2.12, 3.5, 8.1, 8.3, 10.2
Commercial Building Telecommunications Cabling	
TIA-942	9.2
Tier I Data Center: Basic	9.5
Tier II Data Center: Redundant Components	9.6
Tier III Data Center: Concurrently Maintainable	9.6
Tier IV Data Center: Fault Tolerant	9.6
Workstation Multimedia Outlet	8.9
Telemetry	4.2
Test Equipment	10.13
Test and Documentation	10.1-10.15
Fiber Talk Set	10.14
Optical Sources	10.5, 10.7
Optical Power Meters	10.14
OTDR	10.8-10.10, 10.12-10.15
smallTALK® Fiber Communicator	10.14
Visual Fault Locator	10.14
Testing	10.1-10.15
Tight-Buffered Cables	5.3
Token Ring	2.2
Topology	2.3
Transmitters	3.2

Index

Trouble Shooting	10.12-10.14
Universal Module Method	2.8
UV-Cured	7.6
Vertical Rise (See Maximum Vertical Rise)	
Video	4.2
Video Surveillance Systems	1.5
Voice	4.2
Wall-Mountable Hardware	8.10, 8.11
Wavelength	3.2-3.4
Work Area Outlet	8.9



Corning Cable Systems



Fiber Cabling Solutions for Premises Networks

Corning Cable Systems LLC

PO Box 489
Hickory, NC 28603-0489 USA
t 800 743 2675
f 828 901 5973
International +1-828-901-5000

www.corning.com/cablesystems

Corning Cable Systems reserves the right to improve, enhance and modify the features and specifications of Corning Cable Systems products without prior notification. ALTOS, Crimp & Go, FREEDM, LANscape, LID-SYSTEM, MIC, miniMass, TBII and UniCam are registered trademarks of Corning Cable Systems Brands, Inc. CamSplice, Elite, Lite, LSZH, OptiVisor, Pretium, Plug & Play, QUICK-SEAL, Splice Pak and Universal are trademarks of Corning Cable Systems Brands, Inc. Desk-Link and LST are trademarks of Corning Cable Systems LLC. Discovering Beyond Imagination is a trademark of Corning Incorporated. MTP is a registered trademark of USConec, Ltd. ST is a registered trademark of Lucent Technologies. smallTALK is a registered trademark of GN Nettekst (New York) Inc. ESCON is a registered trademark of International Business Machines Corporation. All other trademarks are the properties of their respective owners. Corning Cable Systems is ISO 9001 certified. © 2002, 2005 Corning Cable Systems. All rights reserved. Published in the USA. LAN-164CD-EN / November 2005 / 25M