

Cable Types	No Epoxy/No Polish UniCam® Connectors				Epoxy & Polish Connectors		
	LC Junior	MT-RJ	SC/ST® Compatible/FC/LC Senior	MTP	Anaerobic or GIC	Heat Cure	UV GIC
<b>Single Fiber Cable</b> (1.6, 2.0, or 2.9 mm)							
<b>Zip Cord</b> (1.6, 2.0, or 2.8 mm)							
<b>MIC® &amp; Armored MIC</b> (2F-24F)							
<b>UMIC</b> (24F-144F) & <b>Armored UMIC</b> (24F-72F)							
<b>Fanout Cables</b> (2F-24F) (1.6, 2.0, or 2.9 mm)							
<b>FREEDM® One</b> (Tight Buffered)							
<b>FREEDM or ALTOS®</b> (Loose Tube)							
<b>ALTOS Lite™, Single or Double Armored</b>							
<b>Ribbon Interconnect</b> (jacketed ribbon)							
<b>Loose Tube Ribbon</b> (bare ribbon)							

900 µm only (0.5 lbs ≤ 0.2 dB Δ)
900 µm OR jacketed cable (15 lbs ≤ 0.2 dB Δ)
Buffer Tube Fanout Kit "required" (0.5 lbs ≤ 0.2 dB Δ)
900 µm only (0.5 lbs ≤ 0.2 dB Δ) or Spider Fanout kit "optional" (15 lbs ≤ 0.2 dB Δ)
BTF Kit "required" (0.5 lbs ≤ 0.2 dB Δ) or Spider Fanout kit "required" (15 lbs ≤ 0.2 dB Δ)
Not Recommended